


2.2 Flexible Cable Entry Grommets for Cables without Connectors




Fast and easy, partially tool-free assembly



High flexibility when routing rigid cables



Up to IP66/IP68 rated protection



For metric cut-outs M25 - M85 (KEL-DPF)

Compact, space-saving design



Due to high elasticity also suitable for routing preassembled cable lugs/terminals.

Product Range



KEL-DPF

KEL-ULTRA flex

KEL-JUMBO flex

Chapter Content 2.2



Cable entry grommets | UL type 4X
M25 - M85, for cable diameters
up to 70 mm

KEL-DPF

92



Cable entry grommets | UL type 12
screw mounting, for cable diameters
up to 115 mm

KEL-ULTRA flex

93



Cable entry grommets | UL type 12
screw mounting, for cable diameters
up to 68 mm

KEL-JUMBO flex

94

KEL-DPF

Cable Entry Grommets



Product Description

The KEL-DPF was developed particularly for routing large or unknown sizes of cables into an enclosure or machine (max. cable diameter 70 mm). Due to the flexibility and unique pyramid shape, cable entry and flexible positioning is much easier compared to using conventional cable glands. Also perfect for bundling or restraining large cables.

Cutting of DPF grommets:

Cable diameter less 25%. The corresponding diameters are marked on the grommet.

It is recommended that additional strain relief be provided for cables as part of the installation.

Advantages & Benefits

- Quick and tool-free assembly
- It is possible to install rigid cables at angles
- Suitable for metric cut-outs
- Polyamide locknuts are included in the shipment

Specifications

Material	Thread frame: Polyamide (PA) Pyramid: Elastomer
Color	<input type="checkbox"/> gray (similar RAL 7035) <input checked="" type="checkbox"/> black
Flame class	UL94-Vo
IP rating	IP66/IP68 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E) UL type 4X (acc. to UL 50E)
Operating temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free
Thread length	14 mm / 0.551"
Cut-out dimensions	Metric sizes

Accessories

FP Flanged plates	178 - 183
MP Module plates	174 - 175

Type	Order No.	Thread metric	External diameter	Clamping range	PU
KEL-DPF 25 3-12	<input type="checkbox"/> 42652	M25 × 1.5	39 mm 1.535 "	3 - 12 mm 0.126 - 0.472 "	5
	<input checked="" type="checkbox"/> 50652				
KEL-DPF 32 6-18	<input type="checkbox"/> 42653	M32 × 1.5	46 mm 1.811 "	6 - 18 mm 0.236 - 0.709 "	5
	<input checked="" type="checkbox"/> 50653				
KEL-DPF 40 12-27	<input type="checkbox"/> 42654	M40 × 1.5	54 mm 2.126 "	12 - 27 mm 0.472 - 1.063 "	5
	<input checked="" type="checkbox"/> 50654				
KEL-DPF 50 22-36	<input type="checkbox"/> 42655	M50 × 1.5	64 mm 2.52 "	22 - 36 mm 0.866 - 1.417 "	5
	<input checked="" type="checkbox"/> 50655				
KEL-DPF 63 27-50	<input type="checkbox"/> 42656	M63 × 1.5	77 mm 3.031 "	27 - 50 mm 1.063 - 1.969 "	5
	<input checked="" type="checkbox"/> 50656				
KEL-DPF 75 39-60	<input type="checkbox"/> 42657	M75 × 1.5	89 mm 3.504 "	39 - 60 mm 1.535 - 2.362 "	1
	<input checked="" type="checkbox"/> 50657				
KEL-DPF 85 48-70	<input type="checkbox"/> 42658	M85 × 2	99 mm 3.898 "	48 - 70 mm 1.89 - 2.756 "	1
	<input checked="" type="checkbox"/> 50658				

Wrenches

for M75/M85 plastic locknut

For mounting the new KEL-DPF sizes we offer suitable wrenches with widths M75 and M85 for plastic locknuts. Material: aluminum

M75: Order No.61436 | M85: Order No. 61437 | PU: 1



* Only valid for gray product types

KEL-ULTRA flex

Cable Entry Grommets



Type	Order No.	Sealing range	PU
KEL-ULTRA flex 1 incl. fixing screws	42630	25 - max. 90 mm cable diameter 0.984 - max. 3.543	1
KEL-ULTRA flex 2 incl. fixing screws	42631	75 - max. 115 mm cable diameter 2.953 - max. 4.528 "	1

Product Description

The KEL-ULTRA flex is designed as a cable entry grommet for any large cable or conduit that is difficult to manage. The KEL-ULTRA flex comes in two sizes and is ideal for routing and sealing cables and conduits with a diameter from 25 to 115 mm. Due to the high flexibility of the elastomer pyramid, inserting large, thick cables with KEL-ULTRA flex is easier than using standard cable glands.

After inserting the cable or conduit, the KEL-ULTRA flex is quickly and easily mounted with the metal ring and screws. This ring enables a circular fixing and sealing of the grommet at the enclosure wall. The ring is supplied with each KEL-ULTRA flex. Cutting of grommets: Cable diameter less 25%. It is recommended that additional strain relief be provided for cables as part of the installation.

Advantages & Benefits

- Quick assembly
- Grommets allow for easy orientation and seal of rigid cables.
- IP66 / up to UL type 12 rating

Specifications

Material	Pyramid: Elastomer Fixing metal ring: Steel, zinc-plated Blank plate: Steel, zinc-plated
Flame class	UL94-Vo
IP rating	IP66, when fastened with 8 screws (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Operating temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimension	Round, Ø-cable +30%, max. Ø 140 mm / 5.512 "

Accessories

MP Module plates	174 - 175
BPM Blank plates	185

KEL-JUMBO flex

Cable Entry Grommets



IP54



Product Description

The KEL-JUMBO flex is a flexible cable entry grommet for cables without connectors with a diameter range from 27 - 68 mm.

They are ideal for the routing supply cables into the electronic enclosures.

Cutting of KEL-JUMBO flex grommets:
Cable diameter less 25%. The corresponding diameters are marked on the grommet.

It is recommended that additional strain relief be provided for cables as part of the installation.

Advantages & Benefits



- Quick assembly
- Grommets allow dynamic and flexible movement of rigid cables
- Compact installation area (88 × 88 mm / 3.465 × 3.465 ")

Specifications

Material	Frame: Polyamide (PA) Pyramid: Elastomer
Flame class	UL94-Vo
IP rating	IP54
UL type rating	UL type 12 (acc. to UL 50E)
Operating temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	Round, \varnothing -cable +20%

Accessories

MP Module plates	174 - 175
BP Blank plates	184 - 186

Description	Type	Order No.	Clamping range	PU
	KEL-JUMBO flex 27-48	42614	27 - 48 mm 1.063 - 1.89 "	1
	KEL-JUMBO flex 47-68	42616	47 - 68 mm 1.85 - 2.677 "	1